



# WATERPROOFING

## MiraSTOP™ PF

### Description

MiraSTOP PF is a high-performing Pump Flush used to flush, clean, and prime polyurethane injection pumps. This non-flammable, solvent-free, non-hazardous, non-corrosive cleaning agent is compatible with MiraSTOP CG-F and CG-HS Chemical Grouts.

### Installation

Contact CCW or Henry® Technical Services, or the pump manufacturer for proper flushing and cleaning procedures.

### Packaging

MiraSTOP PF is supplied in 5-gallon metal pails, 36 pails (180 gallons) per pallet.

### Availability

Available through local CCW and Henry Representatives or Distribution. Visit [www.carlisleccw.com](http://www.carlisleccw.com) or [www.henry.com](http://www.henry.com) to contact us, or select "Find a Rep or Distributor."

### Physical Properties

Property	Typical Value	Test Method
Appearance	Clear Liquid	
Viscosity	100 cps	ASTM D-1638
Specific Gravity	0.97	ASTM D-1475
Flash Point	>400°F (204°C)	ASTM D-92
Boiling Point	>480°F (248°C)	

### Limitations

Opened containers must be handled properly to prevent moisture contamination.

### Warnings and Hazards

Review Safety Data Sheets before handling (available online at [carlisleccw.com](http://carlisleccw.com) or [www.henry.com](http://www.henry.com)).

Avoid contact with eyes and skin. Wear proper protective gloves, clothing, and eye/face protection.



### Storage

Store in original sealed containers at temperature between 60-90°F (15-32°C).

Always store pump flush in a protected and dry location in original, unopened containers. Do not store in direct sunlight or in temperatures below 50°F (10°C) or above 86°F (30°C).

When stored at temperatures 50-86°F (10-30°C) in the original, unopened containers, shelf life for the pump flush is 12 months.

### Disposal

Pump flush must be handled and disposed in accordance with local, state, and federal regulations.

### Limited Warranty

Carlisle Coatings & Waterproofing Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the materials or refund its purchase price. This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever. The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.