

NOTES:

1. SPACE WASHER WITH FASTENER 12" O.C. AT WINDOW PERIMETER.

5/8" TYPE X INTERIOR GYPSUM SHEATHING

STEEL OR FIRE TREATED WOOD STUDS

FIRE TREATED LUMBER BUCK (OPTIONAL)

COMPATIBLE SEALANT WITH BACKER ROD. REF CCW MEMBRANE AIR BARRIER DETAIL -0A.

EXTERIOR SHEATHING

CCW MEMBRANE AIR BARRIER

R2+ SILVER, MATTE, OR SHEATHE

EXTERIOR CLADDING (REF R2-0B, R2-0C AND R2-0D)

CCW-705 TWF

WEEP HOLES 24" O/C

WASHER WITH FASTENER OR OTHER MECHANICAL ATTACHMENT (REF R2-0A)

METAL DRIP EDGE. KEEP 705 TWF BACK 1/2" MIN. FROM EXTERIOR

DETAIL IS INTENDED TO BE A GUIDE FOR THE INSTALLATION OF CCW PRODUCTS ONLY. DETAIL SHOWN IS SUITABLE FOR USE IN NFPA 285 WALL ASSEMBLIES. USE WALL ASSEMBLY COMPONENTS AS LISTED IN R2-0B, R2-0C AND R2-0D DETAILS.

R2-5C

POLYISO INSULATION  
PUNCHED WINDOW - HEAD

**CARLISLE**  
COATINGS & WATERPROOFING

© 2015 CARLISLE CORPORATION